



USISIVAČ – SUVO USISAVANJE - PORTABL

FOX

SNAGA MAX

1200

W

VODENI STUB

1940

mmH2O

PROTOK VAZ.

108

m³/h

KAPACITET TANKA

6

l



EKSLUZIVNE KARAKTERISTIKE

- ▶ IDEALAN ZA USISAVANJE SITNE PRAŠINE I OHLAĐENOG PEPELA
- ▶ PROGODAN ZA ČIŠĆENJE NAKON MANJIH RENOVIRANJA ILI POSLOVA ODRŽAVANJA ČISTOĆE

NAJČEŠĆA UPOTREBA

HOREKA



MALOPRODAJA



POLJOPRIVREDA



TEHNIČKA OPREMA



AUTOMOBILIZAM



SPECS



"EASY PUSH" FILTER SISTEM ČIŠĆENJA RADI ODRŽAVANJA PERFORMANSI



ODLAGANJE PRIBORA U PANELU ZA PRIBOR



BEZ STRESA I MAKSIMALNI KONFORT ZAHVALJUJUĆI KOMPAKTNOM DIZAJNU, ERGONOMSKOM RUKOVANJU I KAIŠA-NARAMENICE.

TEHNIČKI PODACI

| | | |
|--|--------------------|-------------|
| Šifra | | FOX |
| PERFORMANSE | | ASDO05743 |
| Korišćenje | | DRY |
| Motor | | 1 |
| Snaga | W | 1200 max |
| Napon | V | 220-240 |
| Vodeni stub | mmH ₂ O | 1940 |
| Protok vazduha | m ³ /h | 108 |
| Kapacitet tanka/Materijal | l | 6/plastic |
| Dužina kabla | m | 5 |
| Jačina buke | dB (A) | 69 |
| (EN 60704-1; EN 60704-2-1; IEC 60335-2-69) | | |
| Prečnik za pribor | mm | 32 |
| Dimenzija (LxWxH) | mm | 390x280x230 |
| Težina | Kg | 3 |

STANDARDNA OPREMA

ŠIFRA: TBFX00985
FLEXIBILNO CREVO 1 M
W/ ZAKRIVLJENA
DRŠKA I REGULATOR
PROTOKA VAZDUHA
Ø32 mm



ŠIFRA: MPVR10345
PLJOSNATI NASTAVAK I
OKRUGLA ČETKA Ø32
mm



ŠIFRA: PVVR00343
REMEN ZA RAME



ŠIFRA: FTDP00626
FILTER KERTRIDŽ



DODATNI PRIBOR

ŠIFRA: MPVR07311
TELESKOPSKA PLASTIČNA
CEV
Ø32 mm



ŠIFRA: SPPV01765
ČETKA SA DUPLOM NAMENOM
Ø32 mm

